

XYLO

flooring

HOLLAND PARK COLLECTION

Technical Data Sheet - LVT Flooring-3.0/0.7mm

Items	Property		Test Method Standard	Review in accordance with Standard
1	Heavy Commercial		EN ISO 10582	Wear layer 0.7mm
2	Dimensional	Length	EN ISO 24337	±0.40mm
		Width		±0.05mm
3	Overall Thickness		EN ISO 24337	Average ± 0.1 mm
4	Squareness		EN ISO 24337	≤0.15mm
5	Straightness		EN ISO 24337	≤0.10mm
6	Wear resistance		EN660-2	Group T
7	Reaction to fire		EN13501-1	Bfl-s1
8	Slip resistance		DIN 51130	≥R11
9	Light Stability		ISO 105-B02:2014 Method 3	≥6
10	Residual indentation		ISO24343	≤0.1mm
11	Dimensional stability		EN434	X direction: ≤0.08%
				Y Direction: ≤0.08%
12	Curling			≤0.30mm
13	Peel resistance		EN431	≥70N/5cm
14	Burning cigarette test		EN1399:1997 Method B	Rating 3: Moderate change of gloss and moderate brown stain

Dimensions 3 x 122 x 610mm
Packed 2.083m²
Installation See Box Inlay
Fitting Glue Down
wear Layer 0.7mm

Warranty
 Residential Lifetime
 Medium Commercial 15 years
 Heavy Commercial 5 years

